

- MARINE & TECHNICAL FABRICS
- SAILCLOTH
- HARDWARE & ACCESSORIES
- ACRYLICS
- OUTDOOR FURNITURE FABRICS



Ecosued

Technical Specification

Fabric Details

COMPOSITION	
SURFACE	Polyester 100%
BACKING	Polyester 67% / Cotton 33%
WIDTH	145cm ± 2%
WEIGHT	460 g/ml.
WATER REPELLANCY	Fluorochemical Treatment
STRENGTH RESISTANCE (UNE 40 085/1:75)	WARP >400N WEFT >400N
BREAKING STRENGTH (UNE 40 085/1:75)	WARP 51% WEFT 61%
TEAR STRENGTH (UNE 40 404:79)	WARP >35N WEFT >35N
ABRASION RESISTANCE (BS 5690:91)	40,000 Cycles
SEAM SLIPPAGE (BS 3320:70)	WARP >6mm WEFT >6mm
FASTNESS TO RUBBING (DRY AND WET) (UNE EN ISO 105X12:96)	WARP >3-4 WEFT >3
FASTNESS TO LIGHT (UNE 40 187:73)	4
FASTNESS OF DYEING TO WATER (UNE EN ISO 105-E01:96)	4-5
WASHING AND DOMESTIC DRYING (CYCLE 8° AT 30°C – DO NOT TUMBLE DRY) – SHRINKAGE	WARP 0.22% WEFT 0.70%
FIRE RETARDANT	CRIB 5 – M1/M2

PLEASE NOTE:

Colours may vary slightly from different batches.