

- MARINE & TECHNICAL FABRICS
- SAILCLOTH
- HARDWARE & ACCESSORIES
- ACRYLICS



Softouch Odyssey

Technical Specification

Softouch using Odyssey fabric is a combination of an Acrylic coated woven polyester and a soft non-woven backer of 100% polyester. With the development of Softouch, fabricating professionals can now provide their customers with a material that has the strength, dimensional stability and water and abrasion resistance they expect from Odyssey along with a scratch resistant that comes from the non-woven backer. Now fabrications, covering sensitive gelcoats, critical printed surfaces and delicate objects, can now provide worry free protection using Softouch.

Fabric Details

COLOURS	Silver Grey / Harbour Blue
WIDTH	150cm / 60"
ROLL LENGTH	45.7mtrs
WEIGHT (FED-STD-191 Method 5041)	11oz/Sq Yard
TENSILE STRENGTH (Test Method – ASTM-D1682-7.01)	Warp – 325 Pounds Weft – 263 Pounds
TONGUE TEAR (Test Method – ASTM-D2261-7.01)	Warp – 30 Pounds Weft – 46 Pounds
TRAPEZOIDAL TEAR (Test Method – ASTM4533-4.08)	Warp – 55 Pounds Weft – 56 Pounds
ELMENDORF TEAR (Test Method – ASTM-D1424-7.01)	Warp – 14 + Pounds Weft – 14 + Pounds
HYDROSTATIC RESISTANCE (8" for 10 minutes) (FED-STD-191 Method 5516)	Initial 0.0 millimetres After weathering 7.0 millimetres

PLEASE NOTE:

Colours may vary slightly from different batches.

Please check colour before cutting cloth as no claim will be accepted on colour variance.

When total protection against colour rub off is required, a protective patch should be sewn in at contact points.